

### Amendments to the Claims

1. (Original) A nozzle for use in generating a pressure jet of liquid wherein the nozzle has a proximal end for connection to a source of pressurised liquid and a distal end at which the pressure jet is generated, characterised in that the nozzle comprises a hollow tube having an axial lumen wherein the lumen has a restriction at the distal end in which an orifice is formed wherein the orifice has a width and an axial length, the width of the orifice being less than that of the lumen, and wherein the hollow tube and the restriction being integrally moulded from a plastic material.
2. (Original) A nozzle as defined in Claim 1 wherein the axial length of the orifice is such that the pressure jet of liquid generated by the nozzle is a surgical pressure jet of liquid.
3. (Currently Amended) A nozzle as defined in Claim 1 ~~or Claim 2~~ wherein the ratio of the axial length of the orifice to its width is 1:1 to 5:1.
4. (Currently Amended) A nozzle as defined in Claim 1 ~~any one of the preceding Claims~~ wherein the nozzle has an additional lumen which is preferably arranged such that the axes of the two lumen are substantially parallel.
5. (Original) A nozzle as defined in Claim 4 wherein the additional lumen is closed at its distal end.
6. (Currently Amended) A nozzle as defined in Claim 4 ~~or Claim 5~~ wherein the additional lumen contains a stiffening element, which is preferably a wire, especially a metal wire.
7. (Currently Amended) A nozzle as defined in Claim 1 ~~any one of Claims 1 to 5~~, wherein the nozzle is sufficiently flexible that the nozzle can be selectively disposed in a curved orientation under manual lateral pressure applied by a surgeon's hand during dissection on a patient.

8. (Currently Amended) A nozzle as defined in Claim 7 which is is sufficiently elastic for the nozzle to return to a straight axially aligned configuration when the lateral pressure is removed.

9. (Currently Amended) A nozzle as defined in Claim 1 ~~any one of the preceding Claims~~ which is composed of a thermoplastic polymeric material, preferably a thermoplastic polycondensate, especially a polyaryletherketone resin.

10. (Cancel).

11. (Currently Amended) A surgical dissection instrument for generating a pressure jet of liquid, the instrument comprising a handpiece, the handpiece being provided with an inlet conduit for receiving a supply of liquid to form a pressure jet and a nozzle as defined in Claim 1 ~~any one of the preceding Claims~~ wherein the nozzle is in fluid communication with the inlet conduit and extends from the handpiece.

12. (Original) An instrument as defined in Claim 11, which has a mechanism for controlling the pressure jet of liquid

13. (Currently Amended) An instrument as defined in Claim 11 ~~or Claim 12~~, wherein the handpiece further comprises an annular collar of plastic material which connects the nozzle to the inlet conduit, the respective ends of the hollow tube and the inlet conduit being push fitted into respective annular ends of the collar and the push-fitted assembly being bonded with adhesive or by thermal bonding.

14. (Currently Amended) An instrument as defined in Claim 11 ~~any one of Claims 11 to 13~~, wherein the handpiece further comprises a manifold at a distal end thereof, the manifold surrounding a proximal portion of the nozzle and defining an internal chamber which is in fluid communication with a suction tube which extends through the handpiece and, in use, is connected to a source of suction.

15. (Original) An instrument as defined in Claim 14, wherein the handpiece further comprises an aspirator tube of plastic material fitted to a distal portion of the manifold, the aspirator tube being cylindrical and surrounding the nozzle.

16. (Original) An instrument as defined in Claim 15, wherein the aspirator tube has a wall thickness such that it is sufficiently flexible that the aspirator tube can be selectively disposed in a curved orientation under manual lateral pressure applied by a surgeon's hand during dissection on a patient.

17. (Currently Amended) An instrument as defined in Claim 15 ~~or Claim 16~~, wherein a proximal end of the aspirator tube is push fitted into the distal portion of the manifold.

18. (Cancel).

19. (Original) A method of manufacturing a nozzle for a surgical dissection instrument for generating a pressure jet of liquid, the method comprising the steps of:

extruding a plastic material to provide a hollow tube having an axial lumen;

moulding an end of the extruded hollow tube to form an integral restriction at the end; and

forming an axially directed orifice which extends through the restriction to the lumen, the width of the orifice being less than that of the lumen.


20. (Original) A method as defined in Claim 19, further comprising the step of cutting the tube to a selected length.

21. (Currently Amended) A method as defined in Claim 19 ~~or Claim 20~~, wherein the nozzle is sufficiently flexible that the nozzle can be selectively disposed in a curved orientation under manual lateral pressure applied by a surgeon's hand during dissection on a patient.

22. (Original) A method as defined in Claim 21, wherein the nozzle is sufficiently elastic for the nozzle to return to a straight axially aligned configuration when the lateral pressure is removed.

23. (Currently Amended) A method as defined in Claim 19 ~~any one of Claims 19 to 22~~, wherein the plastic material is a thermoplastic polymeric material, preferably a thermoplastic polycondensate, especially a polyaryletherketone resin.

Respectfully submitted,



---

Louis Woo, RN 31,730  
Law Offices of Louis Woo  
717 North Fayette Street  
Alexandria, VA 22314  
(703) 299-4090

Date: Aug 16, 2006